



17025 SO. MAIN ST. GARDENA, CA 90248 | 310-327-7474
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 | www.stepstoneinc.com

PRODUCT DATA SHEET

Product Name

Pedestal Set Reinforced Large Scale Narrow Modular Paver

Manufacturer

Stepstone, Inc.
17025 So. Main St.
Gardena, CA 90248
Phone 310-327-7474
Fax 310-217-1424
Toll free 800-572-9029

Product Description

Stepstone has produced high quality precast concrete for over 40 years. Pedestal Set Large Scale Narrow Modular Pavers are precast concrete pavers that come in four standard sizes. They are designed to be used for both commercial and residential applications.

Composition & Materials

Pedestal Set Reinforced Large Scale Narrow Modular Pavers are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

Sizes

Pedestal Set Reinforced Large Scale Narrow Modular Pavers are available in 11-7/8" x 35-7/8" x 2- 1/2", 11-7/8" x 47-7/8" x 2-1/2", 23-7/8" x 35-7/8" x 2-1/2" and 23-7/8" x 47-7/8" x 2- 1/2".

Finishes

Pedestal Set Reinforced Large Scale Narrow Modular Paver available finishes include: Custom aggregates, light, medium, or heavy sandblast.

Colors

Pedestal Set Reinforced Large Scale Narrow Modular Pavers are available in twelve standard colors: Almond, Cafe Brown, Espresso Brown, Caramel, French Gray, Granada White, Iceberg Green, Malibu, Santa Fe Buff, Brick Red, Agave, and Porcelain; custom colors are available upon request.

Technical Data

APPLICABLE STANDARDS

American Society for Testing & Materials (ASTM)
ASTM C33 - *Standard Specification for Concrete Aggregates*
ASTM C39 - *Concrete Compressive Strength*
ASTM C150 - *Standard Specification for Portland Cement*
ASTM C642 - *Water Absorption, Density, Voids in Hardened Concrete*
ASTM C666 - *Rapid Freeze/Thaw Resistance of Concrete*



ASTM C979 - Pigments for Integrally Colored Concrete

ASTM C1028 - Coefficient of Friction

Physical /Chemical Properties

Pedestal Set Reinforced Large Scale Narrow Modular Paver weight is 28 LBS per square foot.

Water absorption: Not more than 5.0 % average, not more than 6.0 % for any individual unit for standard colors.

Unit length, width and height are not more than +/-1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.

Installation

Preparatory Work

Handle and store product according to Stepstone, Inc. recommendations. Follow generally accepted masonry practice.

Methods

Pedestal Set Reinforced Large Scale Narrow Modular Pavers can span over a pedestal system. Sides shall be parallel, with courses straight. Spaces between the pavers shall not be less than 1/8". Reinforced Pavers are to be supported equally and shall be contained at perimeter edges. Slight variations in color and texture of natural materials are normal. Some minor chipping may result from shipping and handling, but is not detrimental to appearance or function.

Building Codes

Pedestal Set Reinforced Pavers are designed to meet or exceed the requirements of the model building codes. Installation must comply with the requirements of all applicable local, state, and national code jurisdictions.

Availability & Cost

Availability

Contact Stepstone, Inc. for information and product availability.

Cost

Budget material cost information may be obtained from the manufacturer at the telephone number above.

Limited Warranty

Pedestal Set Reinforced Large Scale Narrow Modular Pavers are guaranteed against defects in material and workmanship for a period of five years. Unusual abuse and neglect will invalidate the limited warranty. Contact manufacturer for additional information on warranty conditions, duration, and remedies.

Maintenance

Stepstone, Inc. recommends a concrete sealer. Exterior products may be washed periodically to remove dirt, stains, and mildew. Periodic inspection may be advisable in some environments in order to ensure pre-cast components are fixed in place and not subject to movement. In freeze-thaw areas water repellent sealers must be maintained to cover warranty.

Technical Services

The manufacturer maintains a technical sales department offering specifications and engineering calculations for specific products and samples. For assistance contact Stepstone, Inc.