



17025 SO. MAIN ST. GARDENA, CA 90248 | 310-327-7474
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 | www.stepstoneinc.com

PRODUCT DATA SHEET

Product Name

Closed Riser Steptread

Manufacturer

Stepstone, Inc.
17025 So. Main St.
Gardena, CA 90248
Phone 310-327-7474
Fax 310-217-1424
Toll free 800-572-9029

Product Description

Stepstone has produced high quality precast concrete for over 40 years. Closed Riser Steptreads and Starter Nosings are reinforced, engineered, pre-cast concrete units that come in many standard sizes. All Closed Riser Steptreads are to be reinforced with zinc plated welded wire fabric reinforcing. Closed Riser Steptreads are designed for use in commercial and residential applications.

Composition & Materials

Closed Riser Steptreads are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

Sizes

Closed Riser Steptreads are available in standard sizes ranging 11"-12" deep, 36"-48" long with a standard riser height of 7 ³/₄" high.

Finishes

Closed Riser Steptreads available finishes include: Exposed aggregate, Broom finish & Light, Medium, or Heavy Sandblast with or without integral contrasting stripes. Closed Riser Steptreads are available in a Classic or Modern face profile.

Colors

Closed Riser Steptreads are available in twelve standard colors: Almond, Cafe Brown, Espresso Brown, Caramel, French Gray, Granada White, Iceberg Green, Malibu, Santa Fe Buff, Brick Red, Agave, Porcelain; custom colors are available upon request. Integral detectable warning stripes are available in Black, Brown and White.

Technical Data

APPLICABLE STANDARDS
American Society for Testing & Materials (ASTM)
ASTM C33 - *Standard Specification for Concrete Aggregates*
ASTM C39 - *Concrete Compressive Strength*
ASTM C150 - *Standard Specification for Portland Cement*
ASTM C642 - *Water Absorption, Density, Voids in Hardened Concrete*



Precast Solutions Since 1963

17025 SO. MAIN ST. GARDENA, CA 90248 | 310-327-7474
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 | www.stepstoneinc.com

ASTM C666 - *Rapid Freeze/Thaw Resistance of Concrete*

ASTM C979 - *Pigments for Integrally Colored Concrete*

ASTM C1028 - *Coefficient of Friction*

Physical /Chemical Properties

Closed Riser Steptread weight is 3.1 LBS per lineal inch at 12" depth.

Water absorption: Not more than 5.0 % average, not more than 6.0 % for any individual unit for standard colors.

Unit length, width and height are not more than +/- 1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.

Installation

Preparatory Work

Handle and store product according to Stepstone, Inc. recommendations. Follow generally accepted UBC practice.

Methods

Closed Riser Steptreads can be bolted or welded on steel or wood structures. Rise and run for the stairtreads are to be determined by the applicable building codes. Closed Riser Steptreads are designed to meet 100 pound live load, 300 pound concentrated load as per standard building code requirements.

Precautions

Slight variations in color and texture of natural materials are normal. Some minor chipping may result from shipping and handling, but is not detrimental to appearance or function.

Building Codes

Closed Riser Steptreads are designed to meet or exceed the requirements of the model building codes. Installation must comply with the requirements of all applicable local, state, and national code jurisdictions.

Availability & Cost

Availability

Contact Stepstone, Inc. for information and product availability.

Cost

Budget material cost information may be obtained from the manufacturer at the telephone number above.

Limited Warranty

Closed Riser Steptreads are guaranteed against defects in material and workmanship for a period of five years. Unusual abuse and neglect will invalidate the limited warranty. Contact manufacturer for additional information on warranty conditions, duration, and remedies.

Maintenance

Stepstone, Inc. recommends a concrete sealer. Exterior products may be washed periodically to remove dirt, stains, and mildew. Periodic inspection may be advisable in some environments in order to ensure pre-cast components are fixed in place and not subject to movement. In freeze-thaw areas sealers must be maintained to cover warranty.

Technical Services

The manufacturer maintains a technical sales department offering specifications and engineering calculations for specific products and samples. For assistance contact Stepstone, Inc.