



Precast Solutions Since 1963

17025 SO. MAIN ST. GARDENA, CA 90248 | 310-327-7474
13238 SO. FIGUEROA ST. LOS ANGELES, CA 90061 | www.stepstoneinc.com

MATERIAL PRODUCT DATA SHEET

Product Name

Truncated Dome Paver

Manufacturer

Stepstone, Inc.
17025 So. Main St.
Gardena, CA 90248

Phone 310-327-7474
Fax 310-217-1424
Toll free 800-572-9029

Product Description

Stepstone, Inc. has produced high quality pre-cast concrete for over 40 years. Truncated Dome Pavers are precast, A.D.A. compliant, detectable warning surface pavers that are designed to be used in commercial as well as public works applications. Pavers have an aligned dome pattern.

Composition & Materials

Truncated Dome Pavers are hand-made, wet-cast from 5000 PSI hard rock concrete using Type III cement.

Sizes

Truncated Dome Pavers are available in the standard sizes 11-7/8"x11-7/8"x2", 11-7/8"x11-7/8"x4" and 23-7/8"x23-7/8"x2" and 23-7/8"x35-7/8"x2-1/2".

Finishes

Truncated Dome Pavers available finishes include: Domed stippled finish or light sandblast

Colors

Truncated Dome Pavers are available in 14 standard colors: Federal Yellow, Charcoal, Adobe, Agave, Almond, Brick Red, Cafe Brown, Caramel, French Gray, Granada White, Iceberg Green, Kona, Pebble and Porcelain; custom colors are available upon request.

Technical Data

APPLICABLE STANDARDS: American Society for Testing & Materials (ASTM)

ASTM C33 - *Standard Specification for Concrete Aggregates*

ASTM C39 - *Concrete Compressive Strength*

ASTM C150 - *Standard Specification for Portland Cement*

ASTM C642 - *Water Absorption, Density, Voids in Hardened Concrete*

ASTM C666 - *Rapid Freeze/Thaw Resistance of Concrete*

ASTM C979 - *Pigments for Integrally Colored Concrete*

ASTM C1028 - *Coefficient of Friction*

Physical/Chemical Properties

Truncated Dome Paver weight is 22 LBS per square foot. Water absorption: Not more than 6.0 % average, not more than 7.0 % for any individual unit for standard colors. Unit length, width and height are not more than +/- 1/8" from standard dimensions. No unit will differ more than +/-1/8" from the approved samples. Test reports are available upon request. Concrete is non-combustible.

Please contact Stepstone, Inc. for further information.

September 2019